

tic-tech DL Termination Load series are manufactured to match 50 ohms characteristic impedance and effectively provides an RF termination to absorb all incidental power with minimal reflection within the frequency bandwidth up to 3GHz and comes available with N and 7/16 DIN connection.



Model	Frequency	VSWR	Impedance	Power	Temperature	Connector	Dimension	Weight
DL-A300NM/P10	DC-3000MHz	<1.1:1	50 ohm	10 watt	-30°C ~ +60°C	N Male	L62xD35mm	0.12KG
DL-A300NM/P20	DC-3000MHz	<1.1:1	50 ohm	20 watt	-30°C ~ +60°C	N Male	L82xD35mm	0.14KG
DL-A300NM/P30	DC-3000MHz	<1.1:1	50 ohm	30 watt	-30°C ~ +60°C	N Male	L135xD40mm	0.26KG
DL-A300NM/P50	DC-3000MHz	<1.1:1	50 ohm	50 watt	-30°C ~ +60°C	N Male	L136xD50mm	0.40KG
DL-A300NF/P10	DC-3000MHz	<1.1:1	50 ohm	10 watt	-30°C ~ +60°C	N Female	L62xD35mm	0.12KG
DL-A300NF/P20	DC-3000MHz	<1.1:1	50 ohm	20 watt	-30°C ~ +60°C	N Female	L82xD35mm	0.14KG
DL-A300NF/P30	DC-3000MHz	<1.1:1	50 ohm	30 watt	-30°C ~ +60°C	N Female	L135xD40mm	0.26KG
DL-A300NF/P50	DC-3000MHz	<1.1:1	50 ohm	50 watt	-30°C ~ +60°C	N Female	L136xD50mm	0.40KG

