

FREQUENCIES

U.S. CELLULAR 821-896 MHz
All models LT/BS 811 LT/BS 814
LT/BS 812 LT/BS 802

EURO CELLULAR 880-960 MHz
All models LT/BS 911 LT/BS 914
LT/BS 912 LT/BS 902

**LT 811
LT 911**

**BS 802
BS 902**

**LT 802
LT 902**

**BS 812
BS 912**

**LT 812
LT 912**

**BS 811
BS 911**

LT 811 LT 911 BS 811 BS 911

Collinear broadband Cellular Antenna. 4 dB Gain. Frequencies: Mod. LT 911 or BS 911 EURO/CELLULAR 880-960 MHz. Mod. LT 811 or BS 811 U.S. CELLULAR 821-896 MHz. Approx. 4,5 mt = 15 feet RG58U unterminated cable furnished. Connectors: see table "B" for terminated cables with several connectors. Mounting hole size: mm 19 = 3/4 inch. Length: approx. 33 cm = 12 inches. Slim line "LT" or "BS" mount. In Black finish.

LT 802 LT 902 BS 802 BS 902

Quarter wave broadband Cellular Antenna. Unity Gain. Frequencies: Mod. LT 902 or BS 902 EURO/CELLULAR 880-960 MHz. Mod. LT 802 or BS 802 U.S. CELLULAR 821-896 MHz. Approx. 4,5 mt = 15 feet RG58U unterminated cable

furnished. Connectors: see table "B" for terminated cables with several connectors. Mounting hole size: mm 19 = 3/4 inch. Length: approx. 9 cm = 3,5 inches. Slim line "LT" or "BS" mount. In Black finish.

LT 812 LT 912 BS 812 BS 912

Quarter wave broadband globe Cellular Antenna. Unity Gain. Frequencies: Mod. LT 912 or BS 912 EURO/CELLULAR 880-960 MHz. Mod. LT 812 or BS 812 U.S. CELLULAR 821-896 MHz. Approx. 4,5 mt = 15 feet RG58U unterminated cable furnished. Connectors: see table "B" for terminated cables with several connectors. Mounting hole size: mm 19 = 3/4 inch. Length: approx. 7,6 cm = 3 inches. Slim line "LT" or "BS" mount. In Black finish.