

LOW PROFILE TRANSIT ANTENNA

Performance: These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes. (Custom colors are available)

Reliable: The ABS base has an ultrasonically welded brass insert and a gold plated spring loaded contact.

Standard Mounting: These antennas mate with the standard TAD/NMO type mount, providing an excellent moisture seal even when the antenna is removed.

SPECIFICATIONS:

FREQUENCY RANGE:

A1641-406	406-420MHz
A1641-420	420-435MHz
A1641-440	440-450MHz
A1641-450	450-465MHz
A1641-465	465-480MHz
A1641-480	480-495MHz
A1641-490	490-512MHz
A1681-806	806-890MHz
A1681-896	896-960MHz
A1681-915	900-930MHz
A16192	1850-1990MHz
A16245	2400-2500MHz

GAIN:	Unity
IMPEDANCE:	50 ohms
POWER RATING:	200 watts
VSWR:	<2.0:1
HOUSING:	ABS
BASE:	ABS, Ultrasonic brass insert
CONTACT:	Gold plated spring loaded contact
HEIGHT:	2 5/8"
DIAMETER:	1.5"
MOUNTING:	Standard TAD/NMO type
COLOR: - B:	Black
- W:	White



Vertical Pattern

